





























Main



item	Type	Description	Fee MT	Picture
1	CNPA1000PPE200A01	ProMinent CONCEPT Solenoid Diaphragm Dosing Pump IP65 Type Capacity: 1 – 10 bar 0 – 0.74 L/h Dosing head/valves material: Polypropylene Power supply: 230 V, 50/60 Hz, 2m power cable With deaerator, foot valve, dosing valve, 2m PVC hose, 5m PE hose Input: Manual + External Contact + Float Switch	1.6t	
2	CNPA1000PVT200A01	ProMinent CONCEPT Solenoid Diaphragm Dosing Pump IP65 Type Capacity: 1 – 10 bar 0 – 0.74 L/h Dosing head/valves material: PVDF Power supply: 230 V, 50/60 Hz, 2m power cable With deaerator, foot valve, dosing valve, 2m PVC hose, 5m PE hose Input: Manual + External Contact + Float Switch	2t	
3	CNPA1601PPE200A01	ProMinent CONCEPT Solenoid Diaphragm Dosing Pump IP65 Type Capacity: 1 – 16 bar 0 – 1.1 L/h Dosing head/valves material: Polypropylene Power supply: 230 V, 50/60 Hz, 2m power cable With deaerator, foot valve, dosing valve, 2m PVC hose, 5m PE hose Input: Manual + External Contact + Float Switch	1.6t	
4	CNPA1601PVT200A01	ProMinent CONCEPT Solenoid Diaphragm Dosing Pump IP65 Type Capacity: 1 – 16 bar 0 – 1.1 L/h Dosing head/valves material: PVDF Power supply: 230 V, 50/60 Hz, 2m power cable With deaerator, foot valve, dosing valve, 2m PVC hose, 5m PE hose Input: Manual + External Contact + Float Switch	2t	
5	CNPA1002PPE000A01	ProMinent CONCEPT Solenoid Diaphragm Dosing Pump IP65 Type Capacity: 1 – 10 bar 0 – 2.1 L/h Dosing head/valves material: Polypropylene Power supply: 230 V, 50/60 Hz, 2m power cable With deaerator, foot valve, dosing valve, 2m PVC hose, 5m PE hose Input: Manual + External Contact + Float Switch	1.6t	
6	CNPA1002PVT200A01	ProMinent CONCEPT Solenoid Diaphragm Dosing Pump IP65 Type Capacity: 1 – 10 bar 0 – 2.1 L/h Dosing head/valves material: PVDF Power supply: 230 V, 50/60 Hz, 2m power cable With deaerator, foot valve, dosing valve, 2m PVC hose, 5m PE hose Input: Manual + External Contact + Float Switch	2t	
7	CNPA0704PPE000A01	ProMinent CONCEPT Solenoid Diaphragm Dosing Pump IP65 Type Capacity: 1 – 7 bar 0 – 3.9 L/h Dosing head/valves material: Polypropylene Power supply: 230 V, 50/60 Hz, 2m power cable With foot valve, dosing valve, 2m PVC hose, 5m PE hose Input: Manual + External Contact + Float Switch	1.4t	
8	CNPA0704PVT200A01	ProMinent CONCEPT Solenoid Diaphragm Dosing Pump IP65 Type Capacity: 1 – 7 bar 0 – 3.9 L/h Dosing head/valves material: PVDF Power supply: 230 V, 50/60 Hz, 2m power cable With deaerator, foot valve, dosing valve, 2m PVC hose, 5m PE hose Input: Manual + External Contact + Float Switch	2t	
9	CNPb0705PPE000A010	ProMinent CONCEPT Solenoid Diaphragm Dosing Pump IP65 Type Capacity: 1 – 7 bar 0 – 5.2 L/h Dosing head/valves material: Polypropylene Power supply: 230 V, 50/60 Hz, 2m power cable With foot valve, dosing valve, 2m PVC hose, 5m PE hose Input: Manual + External Contact + Float Switch	1.6t	

10	CNPA0705PVT200A01	ProMinent CONCEPT Solenoid Diaphragm Dosing Pump IP65 Type Capacity: 1 – 7 bar 0 – 5.2 L/h Dosing head/valves material: PVDF Power supply: 230 V, 50/60 Hz, 2m power cable With deaerator, foot valve, dosing valve, 2m PVC hose, 5m PE hose Input: Manual + External Contact + Float Switch	2t	
11	CNPA0308PPE200A01	ProMinent CONCEPT Solenoid Diaphragm Dosing Pump IP65 Type Capacity: 1 – 3 bar 0 – 8.5 L/h Dosing head/valves material: Polypropylene Power supply: 230 V, 50/60 Hz, 2m power cable With deaerator, foot valve, dosing valve, 2m PVC hose, 5m PE hose Input: Manual + External Contact + Float Switch	1.6t	
12	CNPA0308PVT200A01	ProMinent CONCEPT Solenoid Diaphragm Dosing Pump IP65 Type Capacity: 1 – 3 bar 0 – 8.5 L/h Dosing head/valves material: PVDF Power supply: 230 V, 50/60 Hz, 2m power cable With deaerator, foot valve, dosing valve, 2m PVC hose, 5m PE hose Input: Manual + External Contact + Float Switch	2t	
13	CNPA0311PPB200A01	ProMinent CONCEPT Solenoid Diaphragm Dosing Pump IP65 Type Capacity: 1 – 3 bar 0 – 11.4 L/h Dosing head/valves material: Polypropylene Power supply: 230 V, 50/60 Hz, 2m power cable With deaerator, foot valve, dosing valve, 2m PVC hose, 5m PE hose Input: Manual + External Contact + Float Switch	1.6t	
14	CNPA0311PPE200A01	ProMinent CONCEPT Solenoid Diaphragm Dosing Pump IP65 Type Capacity: 1 – 3 bar 0 – 11.4 L/h Dosing head/valves material: Polypropylene Power supply: 230 V, 50/60 Hz, 2m power cable With deaerator, foot valve, dosing valve, 2m PVC hose, 5m PE hose Input: Manual + External Contact + Float Switch	1.6t	
15	CNPA0311PVT200A01	ProMinent CONCEPT Solenoid Diaphragm Dosing Pump IP65 Type Capacity: 1 – 3 bar 0 – 11.4 L/h Dosing head/valves material: PVDF Power supply: 230 V, 50/60 Hz, 2m power cable With deaerator, foot valve, dosing valve, 2m PVC hose, 5m PE hose Input: Manual + External Contact + Float Switch	2.1t	
16	CNPA0215PPE200A01	ProMinent CONCEPT Solenoid Diaphragm Dosing Pump IP65 Type Capacity: 1 – 1.5 bar 0 – 14.9 L/h Dosing head/valves material: Polypropylene Power supply: 230 V, 50/60 Hz, 2m power cable With deaerator, foot valve, dosing valve, 2m PVC hose, 5m PE hose Input: Manual + External Contact + Float Switch	1.6t	
17	CNPA0215PVT200A01	ProMinent CONCEPT Solenoid Diaphragm Dosing Pump IP65 Type Capacity: 1 – 1.5 bar 0 – 14.9 L/h Dosing head/valves material: PVDF Power supply: 230 V, 50/60 Hz 14.3W, 2m power cable With deaerator, foot valve, dosing valve, 2m PVC hose, 5m PE hose Input: Manual + External Contact + Float Switch	2.1t	
18	CNPB0223PPE200A010	ProMinent CONCEPT Solenoid Diaphragm Dosing Pump IP65 Type Capacity: 1 – 1.5 bar 0 – 21.9 L/h Dosing head/valves material: Polypropylene Power supply: 230 V, 50/60 Hz 14.3W, 2m power cable With deaerator, foot valve, dosing valve, 2m PVC hose, 5m PE hose Input: Manual + External Contact + Float Switch	1.7t	

19	CNPB0223PVT200A010	ProMinent CONCEPT Solenoid Diaphragm Dosing Pump IP65 Type Capacity: 1 – 1.5 bar 0 – 21.9 L/h Dosing head/valves material: PVDF Power supply: 230 V, 50/60 Hz, 2m power cable With deaerator, foot valve, dosing valve, 2m PVC hose, 5m PE hose Input: Manual + External Contact + Float Switch	2.1t	
20	ALPC0417NPE200A1	ProMinent Alpha Motor Driven Diaphragm Dosing Pump IP65 Type Capacity: 1 – 4 bar 0 – 17 L/h Dosing head/valves material: Acrylic Glass Power supply: 230 V, 50/60 Hz, 2m power cable With deaerator, foot valve, dosing valve, 2m PVC hose, 5m PE hose	3t	
21	BT4b1602PVT2000UA010000	ProMinent Solenoid diaphragm metering pump Beta IP23 Type Capacity: 0 – 2.1 L/h 1 – 16 bar Liquid end/valve material: PVDF With deaerator/PVDF Seal/diaphragm material: PTFE/PTFE coated With foot & dosing valve, 2 m PVC suction tubing, 5m PE discharge tubing Power supply: 200–230 V ± 10 %, 50/60 Hz	4.5t	
22	DLTA1608PVT2000UA11M0ENO	Metering Pump ProMinent Delta Capacity: 0 – 7.8 L/h 1 – 16 bar Liquid end/valve material: PVDF With deaerator/PVDF With foot & dosing valve, 2 m PVC suction tubing, 5m PE discharge tubing alarm relay normally energised 1 x C/O contact 230 V – 8 A Input: Manual& external contact with pulse control& analogue 0/4–20 mA, pH ORP chlorine & DFMA control module	10.5t	
23	VAMC10008PPE000S00	ProMinent VarioC Diaphragm Metering Pumps IP55 Capacity: 1 – 10 bar 0 – 8 L/h Material Liquid end: Polypropylene Electrical power supply: 3 ph, 230 V / 400 V; 50/60 Hz 0.07 kW	4t	
24	VAMC10008PCB000S00	ProMinent VarioC Diaphragm Metering Pumps IP55 Capacity: 1 – 10 bar 0 – 8 L/h Material Liquid end: PVC Electrical power supply: 3 ph, 230 V / 400 V; 50/60 Hz 0.07 kW	4.2t	
25	VAMC10016PVT000S00	ProMinent Vario C Diaphragm Metering Pumps IP55 Capacity: 1 – 10 bar 0 – 16 L/h Material Liquid end: PVDF Electrical power supply: 3 ph, 230 V / 400 V; 50/60 Hz 0.07 kW	6t	
26	VAMC07026PPE000S00	ProMinent VarioC Diaphragm Metering Pumps Capacity: 1 – 7 bar 0 – 26 L/h Material Liquid end: Polypropylene Electrical power supply: 3 ph, 230 V / 400 V; 50/60 Hz 0.07 kW	4t	
27	VAMC07026PCB000S00	ProMinent VarioC Diaphragm Metering Pump IP55 Capacity: 1 – 7 bar 0 – 26 L/h Material Liquid end: PVC, FKM seal Electrical power supply: 3 ph, 230 V / 400 V; 50/60 Hz 0.07 kW	4.2t	
28	VAMC07026PVT000S00	ProMinent Vario C Diaphragm Metering Pump IP55 Capacity: 1 – 7 bar 0 – 26 L/h Material Liquid end: PVDF Electrical power supply: 3 ph, 230 V / 400 V; 50/60 Hz 0.07 kW	6t	
29	VAMC07042PPE000S00	ProMinent VarioC Diaphragm Metering Pump IP55 Capacity: 1 – 7 bar 0 – 42 L/h Material Liquid end: Polypropylene Electrical power supply: 3 ph, 230 V / 400 V; 50/60 Hz 0.07 kW	4t	
30	VAMC07042PCB000S00	ProMinent VarioC Diaphragm Metering Pump IP55 Capacity: 1 – 7 bar 0 – 42 L/h Material Liquid end: PVC Electrical power supply: 3 ph, 230 V / 400 V; 50/60 Hz 0.07 kW	4.2t	
31	VAMC04063PPE000S00	ProMinent VarioC Diaphragm Metering Pump Capacity: 1 – 4 bar 0 – 64 L/h Material Liquid end: Polypropylene Electrical power supply: 3 ph, 230 V / 400 V; 50/60 Hz 0.07 kW	4.4t	

32	VAMC04063PCB000S00	ProMinent VarioC Diaphragm Metering Pump IP55 Capacity: 1 – 4 bar 0 – 64 L/h Material Liquid end: PVC Electrical power supply: 3 ph, 230 V / 400 V; 50/60 Hz 0.07 kW	4.7t	
33	S1BaH10050PVTS000S000	ProMinent Sigma Motor Driven Diaphragm Metering Pump Pump type: 1 – 10 bar 0 – 50 L/h IP55 Material Liquid end/ Seal : PVDF/ PTFE seal Cable and plug: 2 m European Electrical power supply: 3 ph, 230 V/400 V 50 Hz, 0.09 kW	7t	
34	S2BAHM04350PVTS010S000	ProMinent Sigma/2 Motor Driven Diaphragm Metering Pump Pump type: 1 – 4 bar 0 – 350 L/h IP55 Material Liquid end/ Seal : PVDF/ PTFE seal Electrical power supply: 3 ph, 230 V/400 V 50 Hz, 0.25 kW With multilayer diaphragm with rupture detection facility Hydraulic Connection: union nut and PVC insert	10.5t	
38	S2CBH04350PVTS520UA010S0EN	ProMinent Sigma/2 Motor Driven Diaphragm Metering Pump main drive unit 4 bar , 350 l/h PVDF Union nut and PP insert 100 – 240 V 220 W with relief valve, FPM seal, with valve springs With multilayer diaphragm with rupture detection facility Input: Manual& external contact with pulse control& analogue 0/4–20 mA	16t	
39	HP3aH064060SST0000S0000	ProMinent Hydro Hydraulic Diaphragm Metering Pump Type: 4 – 64 bar 0 – 60 L/h Material Liquid end: Stainless Steel 316L Sealing material: PTFE with multilayer diaphragm & rupture signalling Electrical power supply: 3 ph, 230/400 V, 50 Hz	31t	
40	1023085	DulcoTRANS 25/700 PP Barrel pump Capacity: 900 L/h Feed lift max: 5 m External and internal pipe, tap: Polypropylene Drive shaft: HastelloyC Rotor: ETFE Mechanical seal: ceramic oxide/PTFE/carbon Suction Tube Length: 672 mm	5t	
41	1034225	DulcoTRANS 40/1000 Barrel pump Material: polypropylene Capacity:2800 L/h Feed lift max.: 9.5 m Drive shaft: HastelloyC Rotor: ETFE Mechanical seal: ceramic oxide/PTFE/carbon Suction Tube Length: 961 mm	10t	
42	1023087	DulcoTRANS 50/1200 PP Barrel pump Material: polypropylene Capacity: 3750 L/h Feed lift max: 12 m External and internal pipe, tap: Polypropylene Drive shaft: HastelloyC Rotor: ETFE Mechanical seal: ceramic oxide/PTFE/carbon Suction Tube Length: 1,161 mm	18t	
43	1037698 1037699 1037700	Turbidimeter TUC3 IR 0 with AutoClean Ultrasonic Measuring range :0 – 1000.0 NTU Accuracy limit:±2% of displayed value or ± 0.02NTU under 40NTU, Resolution : 0.0001 NTU below 10 NTU Response time : configurable Display : Multiple row LCD display with backlighting Analogue output : 4 ... 20 mA, 600 Ω Communication interface :Bi-directional RS-485, Modbus Maximum water pressure: Integrated pressure regulating valve regulates 1380 kPa (200 PSI). in relation to the flow rate Flow rate: 6 l/h ... 60 l/h Operating temperature:1 ° C ... 50 ° C With Bubble chamber turbidimetry With Calibration kit turbidimetry	24t	

44.1	1035638	<p>Compact controller for pH/ORP IP67 Measurement range pH: 0.00...14 ORP: -1000...+1000 mV Resolution pH: 0,01 pH ORP: 1 mV Correction variable: Temperature for pH via Pt 1000 Control: 1-way controller with selectable control direction (raise/lower) Control outputs: 1 pulse frequency output for control of the metering pump 1 relay (alarm or limit value relay or pulse length control) 1 x analogue output 0/4 ... 20 mA Ambient temperature: -10 ... +60 ° C</p>	5t	
44.2	150041	PH -probe PHEP-112-SE	2.4t	
44.3	DGMa110T000	In-Line Probe Housing Flow monitor module with L/h scale Suitable for pH Sensor	1.5t	
45.1	D1CbW00601000VC1001 G20EN	<p>Chlorine Measuring and Control Unit, type D1Cb Installation Wall mounting (IP 65) Measured variable presetting Chlorine Measured variable connection Standard signal 0/4-20 mA, all measured variables Signal output Analogue signal output 0/4...20 mA Relay control Alarm and 2 limit value relays or 2 timer relays Pump control pumps via pulse frequency</p>	8t	
45.2	792920	Chlorine sensor CLE 3-mA- 2 ppm	5.5t	
45.3	DGMa101T000	In-Line Probe Housing Flow monitor module with L/h scale Suitable for Chlorine Sensor	2t	
		Discharge or Suction or foot valve or injection valve for Concept Beta Gamma and DLTA up to 30 l/h	0.4t	
		Diaphragm for Concept, Beta, Gamma and DLTA up to 30 l/h	0.35 to 0.5t	
		Spare Parts for Concept, Beta, Gamma and DLTA up to 30 l/h	0.8 to 1.1t	
		Spare Parts for Vario	1.1t	
	791715	<p>Multi-Function Valve MFV Size1 1.5/10bar PVT As Relief and BackPressure Valve for metering pumps Concept/Beta/Gamma</p>	0.6t	

	<p>UVCA14P021017E8 1002486 1002468 1022945</p>	<p>UV system Max. flow: 8.7 m³/h Max. pressure: 10 bar Lamp power: 130 W Radiation chamber length: 940 mm Material of Radiation chamber: high-grade Stainless steel 1.4571 Water temp.: 5-40 °C Ambient temp.: 5-40 °C Lamp life time: 8.000-10.000 h Connection nominal diameter: G 2 Application: Drinking water, Process water, Swimming pool water spare parts consist of: 1- UV- lamp 130 W 2-Lamp protection tube Quartz glass 3-UVC sensor W/D red brass silicone free</p>	<p>32t</p>	
	<p>CDLA050P0111E</p>	<p>Chlorine dioxide systems Legio Zon Type CDLa Chlorine dioxide production: 5 g/h With integrated metering pump Intake lance for 10/25 l tank Chlorine dioxide pump: With pump</p>	<p>30t</p>	
	<p>1011301</p>	<p>Hidroten SOLVENT SOCKET OUTLET - 220V ELECTRIC ACTUATOR - PTFE</p>	<p>2t</p>	